

Drester 9000 TT-B

The economical 2-in-1-Gun Cleaner for all paint systems

The Drester 9000-TTB is an economical and space saving gun cleaner for all kinds of spray gun cleaning.

Drester 9000-TTB is a 2-in-1-solution that combines spray gun cleaning for both conventional and water based paint systems in one machine. What you get is a smart, reliable and high performing machine without the risk of cross contamination.

The left part of the machine is a fully enclosed conventional spray gun cleaning section for solvent based paints. After an automated wash cycle with circulating solvent, the spray gun can be rinsed manually with fresh solvent.

The cleaning section for water based paints, the right part of the machine, has a manual cleaning method with an integrated coagulation system. This manual cleaning method is known to give the best cleaning results for spray guns that have been used for water based paints.

Drester 9000-TTB is equipped with the Drester Teflon Diaphragm pumps. These pumps have an outstanding performance and reliability. This makes the machine efficient and ensures minimal loss of solvent. Drester 9000-TTB requires minimal service.



when results count

DRESTER

Two Products in One

THE SOLVENT SYSTEM

Automatic wash cycle

The cleaning section for solvent based paints on the left side is equipped with a Drester Teflon Diaphragm pump for an efficient automatic wash of the spray gun. The automatic wash starts by pressing a foot pedal and runs for 1.5 min with circulating solvent.

Manual clean rinse

An integrated nozzle in the lid is fed with clean solvent for manual rinse. This reduces solvent consumption and removes stubborn deposits. The manual rinse nozzle is also activated by a foot pedal.

Air connection and Spray out funnel

Through an integrated air connection, the spray gun is supplied with compressed air for spray-out facility of the gun. When spraying out the spray gun through the funnel in the lid, solvent goes back into the machine and fumes are removed by the extraction.

Interior and Air flow through the spray gun

The spray cradle is designed to give excellent cleaning results on all types of spray guns, both inside and out. It can easily be removed when cleaning the washing compartment and it can be obtained in a one or two gun version. The wash basin is made of stainless steel with no welded seams. An airflow through the spray gun prevents solvent and particles from entering into the spray gun's air channels during the cleaning cycle.

Flexible Ventilation Connection

The conventional cleaning section has a ventilation connection in the hood that can be attached in different ways, for example to a Drester Airvent (integrated pneumatic extraction) or to a Drester Minivent (electrical fan).

As the ventilation connection is not located in the washing compartment, but up in the hood ("dry ventilation"), the machine can also be connected directly to the central ventilation system in the body shop. N.B. Subject to local regulations. An additional advantage with the dry ventilation is reduced solvent loss.

Moisture trap and Regulator

The moisture trap prevents water and contaminants from penetrating the air system and the regulator ensures correct air pressure.



THE WATER BASE SYSTEM

Brush

It is harder to remove water borne paints from spray guns than conventional paints. That is why the cleaning section for water based paints on the right side has been fitted with a brush for manual pre-wash with recycled water.

Rinse Gun

The rinse gun is designed specifically for effective high-pressure cleaning of the spray gun's paint channels. It is as standard set to use fresh water, but can easily be set for recycled water.

Pump

The Gun Cleaner for water based paints also uses a Drester teflon diaphragm pump for quick and efficient cleaning. This pioneering pump is manufactured of totally non-corrosive materials. The pump feeds recycled water to the cleaning brush.

Agitation and Evacuation

Liquid agitation with air ensures perfect flocculation in a matter of minutes. After filtration the water can be reused or drained off (subject to local Water Authority approval).

There are optional accessories for Drester 9000-TTB such as e.g. Drester Airvent. Contact your dealer for further information.

TECHNICAL DATA

The solvent system

Air supply	7 - 12 bar (100 - 180 psi)
Air consumption	150 l/min (6 c.f.m.) (450 l/min (16 c.f.m. with Drester Airvent 10110)
Extractor diameter	125 mm (5")


The water base system

Liquid volume:	35 litres
Water flow through	
– the pre-wash brush:	1.5-2 l/min
– the rinse gun:	1.5-2 l/min

Measurements

A	1180 mm
B	570 mm
C	1025 mm
D	1470 mm

Weight 85 kg (182 lb)



Hedson Technologies N.A. Inc
Call tollfree on 1-866-478-4328
Tel. 905-339-2800
Fax 416-352-5738
www.hedsonna.com

© Hedson Technologies AB, 2001